

Editorial

Advanced Techniques in Computational Mechanics

Luís Godinho,¹ Daniel Dias-da-Costa,^{2,3} António Tadeu,¹ and Delfim Soares Jr.⁴

¹ CICC, Department of Civil Engineering, University of Coimbra, 3030-788 Coimbra, Portugal

² School of Civil Engineering, The University of Sydney, NSW 2006, Australia

³ INESCC, Department of Civil Engineering, University of Coimbra, 3030-788 Coimbra, Portugal

⁴ Structural Engineering Department, Federal University of Juiz de Fora, 36036-330 Juiz de Fora, MG, Brazil

Correspondence should be addressed to Luís Godinho; lgodinho@dec.uc.pt

Received 9 April 2014; Accepted 9 April 2014; Published 17 April 2014

Copyright © 2014 Luís Godinho et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Computational mechanics has suffered significant developments in the last decades. Novel numerical models have been proposed to model solid and fluid problems, as well as to deal with solid-fluid interaction. Many of these methods are based in a spatial description of the model by points (such as in Meshless methods) or in enrichment strategies of the classic finite element method (such as in the GFEM, XFEM, or EFEM). In many cases, these methods became more efficient and accurate than classical formulations and are very competitive in applied mechanics. All contributions included in this special issue address this challenging and broad topic that we, as editors, have the pleasure to share with the readers. We would like to thank all the authors for their commitment in this issue, as well as the reviewers for their critical and detailed assessment.

This special issue is composed of eight research papers and one review paper. The covered subjects are very broad, including topics such as fluid mechanics, solid mechanics, and optimization problems. Below, a very brief overview of the featured works is given.

The “*Numerical study on the charge transport in a space between concentric circular cylinders*,” by Y. K. Suh and K. H. Baek, addresses what the authors call essential elements of numerical solution methods for the charge transport equations. The authors argue on the uttermost importance of maintaining the conservation property in convective terms because of the numerical accuracy, in particular at low reaction rates.

In the work entitled “*A numerical scheme based on an immersed boundary method for compressible turbulent flows with shocks: application to two-dimensional flows around*

cylinders,” S. Takahashi et al. develop a computational code adopting immersed boundary methods for compressible gas-particle multiphase turbulent flows. A second-order pseudo skew-symmetric form with minimum dissipation models the turbulent flow region, while the monotone upstream-centred scheme for conservation laws scheme is employed in the shock region.

The paper by N. Pochai, entitled “*Numerical treatment of a modified MacCormack scheme in a nondimensional form of the water quality models in a nonuniform flow stream*,” makes use of two mathematical models to simulate water quality in a nonuniform flow stream. The author proposes an alteration to the MacCormack method that is more accurate than the classic method, without a significant loss of computational efficiency.

The work by J. Eliasson, entitled “*Eddy heat conduction and nonlinear stability of a Darcy Lapwood system analysed by the finite spectral method*,” proposes a finite Fourier transform to perform linear and nonlinear stability analyses of a Darcy-Lapwood system of convective rolls. The author shows how many modes are unstable, the wave number instability band within each mode, the maximum growth rate (most critical) wave numbers on each mode, and the nonlinear growth rates for each amplitude as a function of the porous Rayleigh number.

In the paper “*Experiment and application of market-based control for engineering structures*,” by G. Li et al., an experimental study on the vibration control of a single-degree-of-freedom model is carried out to verify market-based control (MBC) strategy effect. The authors’ results reveal that the MBC strategy can reduce both displacement